




MINTRON CCD Color Camera Series.



MODE NO.		7285HNEX	7285HPEX	7385HN	7385HP
TV SYSTEM		NTSC	PAL	NTSC	PAL
IMAGE SENSOR		1/2-inch I.L. CCD Image Sensor		1/3-inch I.L. CCD Image Sensor	
CCD TOTAL PIXELS		~ 410K	~ 470K	~ 410K	~ 470K
SYNC SYSTEM		Internal			Internal
MINIMUM ILLUMINATION		0.2 lux@F1.2 (sense up off)		0.012 lux@F1.2 /20 IRE AGC on B/W 0.0014 lux@F1.2 /20 IRE SENS-UP (32X) B/W	
LENS & VIEW ANGLE		C/CS Mount			C/CS Mount
RESOLUTION		540 TVL			540 TVL
WHITE BALANCE	Mode	ATW / AWC			ATW / AWC
	Range	3200 ~ 9000 °K			3200 ~ 9000 °K
S/N RATIO TYPICAL(MAX)		50dB(MIN)/ 58dB(TYP)(Gamma, Aperture, AGC, OFF)			50dB(MIN)/58dB (TYP)(Gamma, Aperture, AGC, OFF)
SENSE UP		ON / OFF (Preset 8X ,Max 256X by OSD set)			ON / OFF (Preset 8X ,Max 256X by OSD set)
H - MIRROR FUNCTION		OFF / ON (By OSD set)			OFF / ON (By OSD set)
V - MIRROR FUNCTION		OFF / ON (By OSD set)			OFF / ON (By OSD set)
B.L.C. FUNCTION		ON / OFF (By OSD set)			ON / OFF (By OSD set)
ZOOM FUNCTION		OFF / ON (By OSD set)			OFF / ON (By OSD set)
ENHANCE		HIGH / MID (By OSD set)			HIGH / MID (By OSD set)
FLICKLESS		OFF / ON (By OSD set)			OFF / ON (By OSD set)
COLOR BAR		OFF / ON (By OSD set)			OFF / ON (By OSD set)
IR-Cut-FILTER SW					AUTO / EXT-CONT.
GAMMA CORRECTION		0.45 / 1.0 (By OSD set)			0.45 / 1.0 (By OSD set)
GAIN CONTROL		AGC ON / OFF (By OSD set)			AGC ON / OFF (By OSD set)
AUTO IRIS		A.E.S. / DC-IRIS (By OSD set)			A.E.S. / DC-IRIS (By OSD set)
DAY/NIGHT SW		ON/OFF (By OSD set)			ON/OFF (By OSD set)
TITLE		By OSD set			By OSD set
MASK		By OSD set			By OSD set
ELECTRONIC SHUTTER	A.E.S.	1/60~1/120,000 sec.	1/50~1/120,000 sec.	1/60~1/120,000 sec.	1/50~1/120,000 sec.
	FIX.	1/60(50),1/100(120),1/250,1/500,			1/60(50),1/100(120),1/250,1/500,